

BERT-12FK

BERT-12FK (LED, 4 filtros)
Fluorescencia



Imagen referencial de la serie (fabricante).

Para Chile	confirmar
Modelo	BERT-12FK Infinite Fluorescent Microscope
Sistema óptico	Infinite corrected optical system
Cabezal	Seidentopf trinocular, 30° inclination, 48-76mm interpupillary distance
Oculares	Super widefield 10x/25mm (pair)
Revólver	Backward sextuple coded

Especificaciones

Modelo	BERT-12FK Infinite Fluorescent Microscope
Sistema óptico	Infinite corrected optical system
Cabezal	Seidentopf trinocular, 30° inclination, 48-76mm interpupillary distance
Oculares	Super widefield 10x/25mm (pair)
Revólver	Backward sextuple coded
Objetivos	Plan semi-apochromatic (4x/0.10 WD 16.20mm; 10x/0.30 WD 9.60mm; 20x/0.45 WD 2.80mm; 40x/0.70 WD 0.55mm; 100x/1.25 WD 0.21mm)
Platina	Double-layer mechanical, 280x160mm, XY range 75x55mm
Enfoque	Coaxial knobs, 1 µm minimum adjustment
Condensador	N.A. 0.9/0.13, swing-out design
Iluminación	10W white LED, 3500K-6000K adjustable
Fluorescence	FK LED Epi-fluorescent with 4 channels (Blue, Green, UV, Violet)
Filter Sets	FL-B, FL-G, FL-UV, FL-V specifications provided
Special Features	LIM system, ECO function, LCD display

Variantes eléctricas

Chile: confirmar

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

Cromtek · www.cromtek.cl · contacto@cromtek.cl · (+56 2) 3378 0171 · +56 9 4413 5160