

# BM24

BM24 Series Biological Microscopes  
Biológicos



Imagen referencial de la serie (fabricante).

|                           |                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------|
| <b>Para Chile</b>         | 100-240 V (cubre 220 V; frecuencia 50 Hz: confirmar)                                  |
| <b>Cabezal monocular</b>  | inclined at 45°, 360° rotation                                                        |
| <b>Cabezal binocular</b>  | 30° inclined tubes, interpupillary distance adjustable between 48 and 75mm            |
| <b>Cabezal trinocular</b> | 30° inclined tubes, fixed light path beamsplitter 50:50                               |
| <b>Oculares</b>           | WF10x/18mm, WF10x/20mm, WF16x, WF20x available                                        |
| <b>Objetivos</b>          | Achromatic 4x/0.10, 10x/0.25, 20x/0.40, 40x/0.65, 60x/0.85, 100x/1.25 (oil immersion) |

## Especificaciones

|                           |                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------|
| <b>Cabezal monocular</b>  | inclined at 45°, 360° rotation                                                              |
| <b>Cabezal binocular</b>  | 30° inclined tubes, interpupillary distance adjustable between 48 and 75mm                  |
| <b>Cabezal trinocular</b> | 30° inclined tubes, fixed light path beamsplitter 50:50                                     |
| <b>Oculares</b>           | WF10x/18mm, WF10x/20mm, WF16x, WF20x available                                              |
| <b>Objetivos</b>          | Achromatic 4x/0.10, 10x/0.25, 20x/0.40, 40x/0.65, 60x/0.85, 100x/1.25 (oil immersion)       |
| <b>Platina</b>            | Double layer mechanical stage 130 x 130 mm with mechanical 70 x 30 mm X-Y translation stage |
| <b>Enfoque</b>            | Coaxial coarse and fine adjustments with 200 graduations. Precision 2 µm per graduation     |
| <b>Condensador</b>        | Height adjustable Abbe condenser N.A. 1.25 with iris diaphragm                              |
| <b>Iluminación</b>        | High brightness energy-saving LED illumination for long life, brightness adjustable         |
| <b>Alimentación</b>       | Rechargeable AA batteries and integrated 100-240 V power supply                             |

## Variantes eléctricas

**Chile:** 100-240 V (cubre 220 V; frecuencia 50 Hz: confirmar)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

**Cromtek** · [www.cromtek.cl](http://www.cromtek.cl) · [contacto@cromtek.cl](mailto:contacto@cromtek.cl) · (+56 2) 3378 0171 · +56 9 4413 5160