

BM25U

BM25U Series Infinite Biological Microscope
Biológicos



Imagen referencial de la serie (fabricante).

Para Chile	100-240V, 50/60Hz (cubre 220 V / 50 Hz)
Model BM25UB Viewing Head	Seidentopf Binocular, 30° inclination, 55-75mm interpupillary distance, 360° rotation
Revólver	Backward Quadruple
Ocular	Wide Field WF10X/18
Objetivos	Infinite semi-plan achromatic (4x/0.10, 10x/0.25, 40x/0.65 spring-loaded, 100x/1.25 spring-loaded oil)
Platina	Double-layer mechanical, 132x142mm/75x40mm

Especificaciones

Model BM25UB Viewing Head	Seidentopf Binocular, 30° inclination, 55-75mm interpupillary distance, 360° rotation
Revólver	Backward Quadruple
Ocular	Wide Field WF10X/18
Objetivos	Infinite semi-plan achromatic (4x/0.10, 10x/0.25, 40x/0.65 spring-loaded, 100x/1.25 spring-loaded oil)
Platina	Double-layer mechanical, 132x142mm/75x40mm
Enfoque	Coarse & fine coaxial, 0.004mm fine division, 32.7mm coarse stroke, 0.4mm fine stroke, 24mm range
Condensador	NA 1.25 Abbe with iris diaphragm
Iluminación	LED, adjustable brightness
Alimentación	100-240V, 50/60Hz
Model BM25UIB	same specifications as BM25UB except objectives are infinite plan achromatic

Variantes eléctricas

Chile: 100-240V, 50/60Hz (cubre 220 V / 50 Hz)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

Cromtek · www.cromtek.cl · contacto@cromtek.cl · (+56 2) 3378 0171 · +56 9 4413 5160