

BM29

BM29/BM31 Series Biological Microscope
Biológicos



Imagen referencial de la serie (fabricante).

Para Chile	100-240Vac/5Vdc external (cubre 220 V; frecuencia 50 Hz: confirmar)
Modelos BM31	BM31M, BM31B, BM31T, BM31BS, BM31TS, BM31-MU2, BM31LD
Modelos BM29	BM29M, BM29B, BM29T, BM29BS, BM29TS, BM29LD
Ocular	WF10x/18mm (pair)
Objetivos	4x/0.10, 10x/0.25, 40x/0.65, 100x/1.25 (oil), all with anti-fungus treatment
Aumento total	40x-1000x

Especificaciones

Modelos BM31	BM31M, BM31B, BM31T, BM31BS, BM31TS, BM31-MU2, BM31LD
Modelos BM29	BM29M, BM29B, BM29T, BM29BS, BM29TS, BM29LD
Ocular	WF10x/18mm (pair)
Objetivos	4x/0.10, 10x/0.25, 40x/0.65, 100x/1.25 (oil), all with anti-fungus treatment
Aumento total	40x-1000x
Condensador	Abbe N.A. 1.25, pre-centered, focusable with iris diaphragm
Platina BM31	130x140mm, moving range 75x50mm
Platina BM29	120x130mm, moving range 70x30mm
Platina	Vernier scale on both axes, coarse range 25mm/15mm, fine precision 0.002mm
Iluminación	3W LED, brightness adjustable, 60,000+ hours lifespan
Alimentación	100-240Vac/5Vdc external
LCD 9.5"	IMX307 sensor, 2MP, 1920x1080@60FPS
LCD 10.5"	IMX307 sensor, 8MP 4K, 3840x2160@30FPS, WIFI6, Bluetooth 5.0
C-Mount	0.5x standard; 1x/0.3x/0.7x optional

Variantes eléctricas

Chile: 100-240Vac/5Vdc external (cubre 220 V; frecuencia 50 Hz: confirmar)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

Cromtek · www.cromtek.cl · contacto@cromtek.cl · (+56 2) 3378 0171 · +56 9 4413 5160