

IE5600

IE5600 Series Inverted Laboratory Level Microscopes
Invertidos



Imagen referencial de la serie (fabricante).

Para Chile	6V/30W or 5W LED (100V-240V input) (cubre 220 V; frecuencia 50 Hz: confirmar)
Modelo (specs)	IE5600PU
Ocular	WF10×/22mm
Field of View Diameter	22 mm
Objectives (LWD Infinity Plan)	L Plan FL 4X/0.11 (W.D.=12.1mm); L Plan FL 10X/0.25 (W.D.=10.3mm); L Plan FL 20X/0.45 (W.D.=5.8mm); L Plan FL 40X/0.65 (W.D.=5.1mm)
Phase Contrast Objectives	L Plan FL PHP 4X/0.10; L Plan FL PHP 10X/0.25; L Plan FL PHP 20X/0.45; L Plan FL PHP 40X/0.65

Especificaciones

Modelo (specs)	IE5600PU
Ocular	WF10×/22mm
Field of View Diameter	22 mm
Objectives (LWD Infinity Plan)	L Plan FL 4X/0.11 (W.D.=12.1mm); L Plan FL 10X/0.25 (W.D.=10.3mm); L Plan FL 20X/0.45 (W.D.=5.8mm); L Plan FL 40X/0.65 (W.D.=5.1mm)
Phase Contrast Objectives	L Plan FL PHP 4X/0.10; L Plan FL PHP 10X/0.25; L Plan FL PHP 20X/0.45; L Plan FL PHP 40X/0.65
Cabezal	Inclined 45°, interpupillary distance 48-76mm
Revólver	Quintuple
Mechanical Stage	X×Y 210×241mm; round slide Ø110mm; movement range X×Y 128×80mm
Condensador	N.A. 0.3; working distance 72mm (with), 195mm (without)
Iluminación	6V/30W or 5W LED (100V-240V input)
Filters	Blue, Green, Amber/Grey (optional)

Variantes eléctricas

Chile: 6V/30W or 5W LED (100V-240V input) (cubre 220 V; frecuencia 50 Hz: confirmar)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

Cromtek · www.cromtek.cl · contacto@cromtek.cl · (+56 2) 3378 0171 · +56 9 4413 5160