

KOWA Series C-mount USB2.0 CMOS Camera, 1.3MP-16MP

KOWA Series C-mount USB2.0 CMOS Camera, 1.3MP-16MP

Cámaras



Imagen referencial de la serie (fabricante).

Para Chile	DC 5V (USB) (confirmar adaptador 220 V / 50 Hz)
KOWA-16 Sensor	16M/MN3142(C) 1/2.33"(6.18×4.66); Pixel 1.335×1.335 μm; FPS/Resolution 2@4632×3488, 8@2320×1740, 11@1536×1160; Binning 1×1, 2×2, 3×3; Exposure 0.2ms~2000ms
KOWA-10 Sensor	10M/MT9J003(C) 1/2.3"(5.98×4.59); Pixel 1.67×1.67 μm; FPS/Resolution 3.3@3584×2748, 11@1792×1374, 38@896×684; Binning 1×1, 2×2, 4×4; Exposure 0.4ms~2000ms
KOWA-5 Sensor	5.1M/MT9P006(C) 1/2.5"(5.70×4.28); Pixel 2.2×2.2 μm; FPS/Resolution 7@2592×1944, 27@1280×960, 90@640×480; Binning 1×1, 2×2, 4×4; Exposure 0.294ms~2000ms
KOWA-3 Sensor	3.1M/MT9T001(C) 1/2"(6.55×4.92); Pixel 3.2×3.2 μm; FPS/Resolution 12@2048×1536, 32@1024×768, 45@680×510; Binning 1×1, 2×2, 3×3; Exposure 0.244ms~2000ms
KOWA-1 Sensor	1.3M/SC1235(C) 1/3"(4.80×3.60); Pixel 3.75×3.75 μm; FPS/Resolution 25@1280×960, 25@1280×720; Exposure 0.1ms~2000ms

Especificaciones

KOWA-16 Sensor	16M/MN3142(C) 1/2.33"(6.18×4.66); Pixel 1.335×1.335 μm; FPS/Resolution 2@4632×3488, 8@2320×1740, 11@1536×1160; Binning 1×1, 2×2, 3×3; Exposure 0.2ms~2000ms
KOWA-10 Sensor	10M/MT9J003(C) 1/2.3"(5.98×4.59); Pixel 1.67×1.67 μm; FPS/Resolution 3.3@3584×2748, 11@1792×1374, 38@896×684; Binning 1×1, 2×2, 4×4; Exposure 0.4ms~2000ms
KOWA-5 Sensor	5.1M/MT9P006(C) 1/2.5"(5.70×4.28); Pixel 2.2×2.2 μm; FPS/Resolution 7@2592×1944, 27@1280×960, 90@640×480; Binning 1×1, 2×2, 4×4; Exposure 0.294ms~2000ms
KOWA-3 Sensor	3.1M/MT9T001(C) 1/2"(6.55×4.92); Pixel 3.2×3.2 μm; FPS/Resolution 12@2048×1536, 32@1024×768, 45@680×510; Binning 1×1, 2×2, 3×3; Exposure 0.244ms~2000ms

KOWA-1 Sensor	1.3M/SC1235(C) 1/3"(4.80×3.60); Pixel 3.75×3.75 μm; FPS/Resolution 25@1280×960, 25@1280×720; Exposure 0.1ms~2000ms
Spectral Range	380-650nm (with IR-filter)
White Balance	ROI White Balance/Manual Temp-Tint Adjustment
Color Rendering	Ultra Fine Color Engine
SDK	Windows/Linux/macOS/Android (C/C++, C#/VB.NET, Python, Java, DirectShow, Twain)
Recording	Still Picture and Movie
Cooling	Natural
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 60°C
Humidity	30~80% RH (operating); 10~60% RH (storage)
Alimentación	DC 5V via PC USB Port

Variantes eléctricas

Chile: DC 5V (USB) (confirmar adaptador 220 V / 50 Hz)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

Cromtek · www.cromtek.cl · contacto@cromtek.cl · (+56 2) 3378 0171 · +56 9 4413 5160