

# MIV5100

MIV5100 (invertido)  
Metalúrgicos y digitales



|                                    |                                                                                                      |
|------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Para Chile</b>                  | Halogen lamp 6V/30W (confirmar adaptador 220 V / 50 Hz)                                              |
| <b>Modelos</b>                     | MIV5100, MIV5100A                                                                                    |
| <b>Cabezal</b>                     | Trinocular inclined at 30°, interpupillary 48-75mm                                                   |
| <b>Ocular</b>                      | High-point, Extra wide field eyepiece EW10X/20                                                       |
| <b>Aumento</b>                     | Up to 400x                                                                                           |
| <b>Objective Lenses (Standard)</b> | 4X/0.10/∞/- WD 17.3mm;<br>10X/0.25/∞/- WD 10.0mm;<br>20X/0.40/∞/0 WD 5.8mm;<br>40X/0.6/∞/0 WD 2.90mm |

Imagen referencial de la serie (fabricante).

## Especificaciones

|                                        |                                                                                               |
|----------------------------------------|-----------------------------------------------------------------------------------------------|
| <b>Modelos</b>                         | MIV5100, MIV5100A                                                                             |
| <b>Cabezal</b>                         | Trinocular inclined at 30°, interpupillary 48-75mm                                            |
| <b>Ocular</b>                          | High-point, Extra wide field eyepiece EW10X/20                                                |
| <b>Aumento</b>                         | Up to 400x                                                                                    |
| <b>Objective Lenses (Standard)</b>     | 4X/0.10/∞/- WD 17.3mm; 10X/0.25/∞/- WD 10.0mm; 20X/0.40/∞/0 WD 5.8mm; 40X/0.6/∞/0 WD 2.90mm   |
| <b>Revólver</b>                        | Quintuple                                                                                     |
| <b>Platina</b>                         | Plain with slide clips; attachable mechanical stage with X-Y coaxial control (120×78mm range) |
| <b>Focusing</b>                        | Coaxial coarse/fine adjustment; coarse stroke 37.7mm/rotation; fine stroke 0.2mm/rotation     |
| <b>Iluminación</b>                     | Halogen lamp 6V/30W, Kohler illumination                                                      |
| <b>Filters</b>                         | Blue, Yellow, Green, ground glass                                                             |
| <b>Optional</b>                        | Polarization attachment                                                                       |
| <b>Additional Objectives Available</b> | 2.5X, 5X, 50X, 80X, 100X variants                                                             |

## Variantes eléctricas

**Chile:** Halogen lamp 6V/30W (confirmar adaptador 220 V / 50 Hz)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

**Cromtek** · [www.cromtek.cl](http://www.cromtek.cl) · [contacto@cromtek.cl](mailto:contacto@cromtek.cl) · (+56 2) 3378 0171 · +56 9 4413 5160