

ZT40

ZT40 Series Greenough Zoom Stereo Microscope 10x-40x
Estéreo



Para Chile	100-240V (cubre 220 V; frecuencia 50 Hz: confirmar)
Modelos	ZT40B-BL2, ZT40T-BL2, ZT40B-BS2, ZT40T-BS2
Sistema óptico	Greenough type
Zoom Objective Range	1x-4x
Zoom Ratio	4:1
Standard Magnification	10x-40x (extendable to 5x-240x)

Imagen referencial de la serie (fabricante).

Especificaciones

Modelos	ZT40B-BL2, ZT40T-BL2, ZT40B-BS2, ZT40T-BS2
Sistema óptico	Greenough type
Zoom Objective Range	1x-4x
Zoom Ratio	4:1
Standard Magnification	10x-40x (extendable to 5x-240x)
Working Distance	91mm
Oculares	WF10x/22mm (standard); WF15x/16mm, WF20x/12mm, WF25x/9mm, WF30x/8mm (optional)
Interpupillary Distance	55-75mm adjustable
Diopter Adjustment	±5 for both sides
Illumination (BL2 models)	12V/10W halogen, incident & transmitted, adjustable brightness
Illumination (BL2L/CH3 models)	LED (1W or 3W), incident & transmitted, adjustable brightness
Voltage Range	100-240V
Cabecal	Binocular or trinocular, 360° rotating, 45° inclined
Stand Options	BL2, BL2L, CH3 (with illumination) or BS1/BS2 (without illumination)
Focusing Mechanism	Rack and pinion, coarse only, 100mm stroke

Variantes eléctricas

Chile: 100-240V (cubre 220 V; frecuencia 50 Hz: confirmar)

Ficha preparada por Cromtek con información del fabricante (web nbicoe.com página de la familia, leída 2026-10-07 (WebFetch), 2026-10-07). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

Cromtek · www.cromtek.cl · contacto@cromtek.cl · (+56 2) 3378 0171 · +56 9 4413 5160