

# Cambiador de muestras XYZ TW 7450

Cambiadores de muestras



Imagen referencial de la serie (fabricante).

|                                   |                                                                                                         |
|-----------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>Variantes</b>                  | 7 (ver tabla de variantes)                                                                              |
| <b>Para Chile</b>                 | Fuente enchufable 100-240 V, 50/60 Hz, 80 VA: válida para la red chilena (220 V / 50 Hz)                |
| <b>Dimensiones</b>                | 560 x 480 x 600 mm (W x H x D)                                                                          |
| <b>Dimensiones de la gradilla</b> | 495 x 61 x 457 mm (W x H x D)                                                                           |
| <b>Peso</b>                       | approx. 21 kg                                                                                           |
| <b>Peso de la gradilla</b>        | approx. 2,8 kg                                                                                          |
| <b>Alimentación</b>               | plug-in power supply unit of 100 - 240 V, 50/60 Hz, Output voltage: 24 Volt DC, power consumption 80 VA |

## Especificaciones

|                                   |                                                                                                         |
|-----------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>Dimensiones</b>                | 560 x 480 x 600 mm (W x H x D)                                                                          |
| <b>Dimensiones de la gradilla</b> | 495 x 61 x 457 mm (W x H x D)                                                                           |
| <b>Peso</b>                       | approx. 21 kg                                                                                           |
| <b>Peso de la gradilla</b>        | approx. 2,8 kg                                                                                          |
| <b>Alimentación</b>               | plug-in power supply unit of 100 - 240 V, 50/60 Hz, Output voltage: 24 Volt DC, power consumption 80 VA |
| <b>Normas</b>                     | EN 61010-1 (seguridad)                                                                                  |

## Variantes

| Código    | Variante   | Muestras (gradilla) | Bomba de enjuague | Contenido                                                                                                                     |
|-----------|------------|---------------------|-------------------|-------------------------------------------------------------------------------------------------------------------------------|
| 285221400 | TW 7450    | —                   | —                 | Basic unit without titration head and sample rack. With USB connection cable for PC connection, power supply 100-240 V        |
| 285221440 | TW 7450-42 | 42                  | —                 | Basic unit with sample rack TZ 3942 for 42 samples, titration head TZ 3963, rod stirrer TZ 1847 and FEP-hose (5 m), 100-240 V |

| Código    | Variante      | Muestras (gradilla) | Bomba de enjuague | Contenido                                                                                                                                                                                         |
|-----------|---------------|---------------------|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 285221450 | TW 7450-42-MP | 42                  | MP 25             | Basic unit with sample rack TZ 3942 for 42 samples, titration head TZ 3967, rod stirrer TZ 1847, rinsing pump MP 25 and FEP-hose (5 m), 100-240 V                                                 |
| 285221460 | TW 7450-48    | 48                  | —                 | Basic unit with sample rack TZ 3948 for 48 samples, titration head TZ 3964, rod stirrer TZ 1847 and FEP-hose (5 m), 100-240 V                                                                     |
| 285221470 | TW 7450-48-MP | 48                  | MP 25             | Basic unit with sample rack TZ 3948 for 48 samples, titration head TZ 3965, rinsing vessel TZ 3949, rinsing pump MP 25, rod stirrer TZ 1847 and FEP-hose (5 m), 100-240 V                         |
| 285221480 | TW 7450-72    | 72                  | —                 | Basic unit with sample rack TZ 3972 for 72 samples, titration head TZ 3974, rod stirrer TZ 1847 and FEP-hose (5 m), 100-240 V                                                                     |
| 285221490 | TW 7450-72-MP | 72                  | MP 25             | Basic unit with sample rack TZ 3972 for 72 samples, titration head TZ 3974, rinsing vessel TZ 3970, rinsing nozzle TZ 3971, rinsing pump MP 25, rod stirrer TZ 1847 and FEP-hose (5 m), 100-240 V |

Ficha preparada por Cromtek con información del fabricante (xylemanalytics.com (web oficial SI Analytics), 2026-10-08). Datos sujetos a confirmación; un ejecutivo de Cromtek le enviará precio y plazo de entrega.

**Cromtek** · [www.cromtek.cl](http://www.cromtek.cl) · [contacto@cromtek.cl](mailto:contacto@cromtek.cl) · (+56 2) 3378 0171 · +56 9 4413 5160